

## **PLAYNOTE™SOUND TOWER SYSTEM SPECIFICATIONS**

### ***REQUIREMENT: 1 DEDICATED CIRCUIT WITH ISOLATED GROUND***

#### **TOWER SIZE:**

HEIGHT: 29"

WIDTH AT CENTER: 8"

WIDTH AT BASE: 13 7/16"

COLOR: BEIGE

**ETL LISTED** COMMERCIAL AUDIO SYSTEM, RATED INTERIOR or EXTERIOR

**SOUND TYPE:** DIGITAL MP3

32 MINUTE. CHIP STANDARD SOUND CAPACITY REMOVABLE RE-RECORDABLE

OPTIONAL: 64 MINUTE. SOUND CHIP REMOVABLE AND RE-RECORDABLE

MAX. CAPACITY FOR INDIVIDUAL SOUND FILES 2000

**SOUND SETTINGS AVAILABLE:** RANDOM, SEQUENTIAL, OR CONTINUOUS PLAY

**SOUND PLAY SETTINGS:** END OF FILE OR IMMEDIATE PLAY

**AMPLIFIER:** 24W

**SPEAKER:** KLH WEATHER RESISTANT 3 WAY

WOOFER: 4" DYNAMIC W/ POLYPROPYLENE CONE

MIDRANGE: 1 3/4 POLYCARBONATE CONE

TWEETER: 5/8 MYLAR PIEZO CONE

OHMS: 4-6 AVERAGE

FREQ. RESPONSE: 90-20KHz

**SENSORS:** PICKS

MAXIMUM PICKS: 8

AVERAGE LIFE CYCLE: 20,000,000 ACTUATION'S

OPERATING TEMPERATURE: -20F TO 140F

SIGNAL TYPE: PULSE

VOLTAGE: 3VDC .25 ma, MAX. 250ma

DIAMETER: 5/8

LENGTH: 4"

WIRE LENGTH: 17' GRAY, UL LISTED STYLE 2517

MATERIAL: GRAY PVC

**TRANSFORMER:** 15V AC 60W W/ 3' PLUG-IN CORD, UL RATED INTERIOR OR EXTERIOR,  
SET INSIDE OF TOWER FRAME

**POWER CABLE:** 3' FROM TRANSFORMER TO PLUG.

**WARRANTY:** 1 YEAR FROM DATE OF INSTALLATION (SEE WARRANTY FOR DETAILS)

**WARNING NOTICE:** DO NOT ANCHOR OR BOLT THE INTERIOR ALUMINUM FRAME TO ANYTHING

**SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE**

PNSTSYSTEMSPEC.DOC